

Description

Impact-Rated Bollard. IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board.

Crash rated for small vehicles travelling up to 40mph (SC40), pick-up vehicles travelling up to 40mph (PU40), and medium-duty vehicles travelling up to 30mph (M30).

Luminaire spacing up to 35 ft; ideal for pathway lighting applications.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			





Electrical description

Surge protection	Integral 10kV Surge Protector
Energy efficiency	This is a new product release and may have an extended lead time.



Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [C60] symmetric distribution	 3000K	18 W 26 W
 [R65] Type IV Medium	 4000K	13 W 9 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-9091	LED-6/18W/3000K	825 lm	18 W	80
	114-9091	LED-6/18W/3000K	825 lm	18 W	80
	114-9092	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9092	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9093	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9093	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-6507	LED-6/26W/4000K	1103.3 lm	26 W	80
	114-6506	LED-6/26W/4000K	1103.3 lm	26 W	80
 <p>[R65] Type IV Medium</p>	114-6512	LED-3/9W/3000K	519.7 lm	9 W	80
	114-6513	LED-3/9W/3000K	519.7 lm	9 W	80
	114-6515	LED-3/9W/4000K	543.9 lm	9 W	80
	114-6514	LED-3/9W/4000K	543.9 lm	9 W	80
	114-6509	LED-3/13W/3000K	664.7 lm	13 W	80
	114-6509	LED-3/13W/3000K	664.7 lm	13 W	80
	114-6511	LED-3/13W/4000K	694.9 lm	13 W	80
	114-6510	LED-3/13W/4000K	694.9 lm	13 W	80