

**Description**

IP66, Class I. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional 2200 K version available. To be specified at time of ordering.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

## Specifications

### Material description

---

Body	Marine-grade, all-aluminium construction		
Lens	Polycarbonate		
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Power supply	230V / 50 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10) available on request
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

---

**Options**

**Light distribution**



[C60] symmetric distribution




[R65] rectangular, side throw

**Colour temperature**



3000K



4000K



2700K

**Nominal Watt**



18 W

26 W

9 W

13 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-9183	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9179	LED-6/18W/3000K	825 lm	18 W	80
	114-9180	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9184	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9181	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9182	LED-6/26W/4000K	1103.3 lm	26 W	80
 <p>[R65] rectangular, side throw</p>	114-9187	LED-3/9W/2700K	495.5 lm	9 W	80
	114-9173	LED-3/9W/3000K	519.7 lm	9 W	80
	114-9174	LED-3/9W/4000K	543.9 lm	9 W	80
	114-9188	LED-3/13W/2700K	628.5 lm	13 W	80
	114-9175	LED-3/13W/3000K	664.7 lm	13 W	80
	114-9176	LED-3/13W/4000K	694.9 lm	13 W	80