

### Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional 2200 K version available. To be specified at time of ordering.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction																
Lens	Polycarbonate																
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9006</b></td><td><b>RAL9016</b></td><td><b>RAL7016</b></td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Traffic white</td><td>Anthracite grey</td></tr><tr><td><b>RAL9007</b></td><td></td><td></td><td></td></tr><tr><td>Grey aluminium</td><td></td><td></td><td></td></tr></table>	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9016</b>	<b>RAL7016</b>	Signal black	White aluminium	Traffic white	Anthracite grey	<b>RAL9007</b>				Grey aluminium			
<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9016</b>	<b>RAL7016</b>														
Signal black	White aluminium	Traffic white	Anthracite grey														
<b>RAL9007</b>																	
Grey aluminium																	
Gasket	Silicone CCG® Controlled Compression Gasket																
Fasteners	PCS Polymer Coated Stainless Steel Hardware																
Ingress protection	IP66																
Impact resistance	IK10																
Corrosion resistance	5CE																

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV
Energy efficiency	C-D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

## Options

### Light distribution



[C60] symmetric distribution




[R65] rectangular, side throw

### Colour temperature



3000K



4000K



2700K

### Nominal Watt



18 W

26 W

9 W

13 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-0176	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9179	LED-6/18W/3000K	825 lm	18 W	80
	114-9180	LED-6/18W/4000K	863.4 lm	18 W	80
	114-0177	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9181	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9182	LED-6/26W/4000K	1103.3 lm	26 W	80
 <p>[R65] rectangular, side throw</p>	114-0178	LED-3/9W/2700K	495.5 lm	9 W	80
	114-9173	LED-3/9W/3000K	519.7 lm	9 W	80
	114-9174	LED-3/9W/4000K	543.9 lm	9 W	80
	114-0179	LED-3/13W/2700K	628.5 lm	13 W	80
	114-9175	LED-3/13W/3000K	664.7 lm	13 W	80
	114-9176	LED-3/13W/4000K	694.9 lm	13 W	80