

Description

IP66, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two-sided light output versions for 360° symmetric distribution.

One-sided light output versions with 'rearward glow' feature. Ideal for pathway lighting applications. Luminaire spacing up to 5-8 m. Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, all-aluminium construction		
Lens	Polycarbonate		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	10/10kV (SP10) available on request
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution



[C60] symmetric distribution




[R65] rectangular, side throw

Colour temperature



3000K



4000K



2700K

Nominal Watt



18 W

26 W

9 W

13 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-9192	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9091	LED-6/18W/3000K	825 lm	18 W	80
	114-9092	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9193	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9093	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9094	LED-6/26W/4000K	1103.3 lm	26 W	80
 <p>[R65] rectangular, side throw</p>	114-9095	LED-3/9W/2700K	495.5 lm	9 W	80
	114-9085	LED-3/9W/3000K	519.7 lm	9 W	80
	114-9086	LED-3/9W/4000K	543.9 lm	9 W	80
	114-9096	LED-3/13W/2700K	628.5 lm	13 W	80
	114-9087	LED-3/13W/3000K	664.7 lm	13 W	80
	114-9088	LED-3/13W/4000K	694.9 lm	13 W	80