

**Description**

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens, CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Luminaire spacing up to 35 ft; ideal for pathway lighting applications.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

**Specifications**

**Material description**

Body	Marine-grade all-aluminum construction			
Lens	Polycarbonate			
Colors	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL8019</b>	<b>RAL9007</b>
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

**Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	Integral 10kV Surge Protector
Energy efficiency	This is a new product release and may have an extended lead time.

**Additional information**

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

**Light distribution**



[C60] symmetric distribution




[R65] Type IV Medium

**Color temperature**



3000K



4000K



2700K

**Nominal Watt**



18 W

26 W

9 W

13 W

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-9192	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9091_us	LED-6/18W/3000K	825 lm	18 W	80
	114-9092_us	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9193	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9093_us	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9094_us	LED-6/26W/4000K	1103.3 lm	26 W	80
	 <p>[R65] Type IV Medium</p>	114-9095	LED-3/9W/2700K	495.5 lm	9 W
114-9085_us		LED-3/9W/3000K	519.7 lm	9 W	80
114-9086_us		LED-3/9W/4000K	543.9 lm	9 W	80
114-9096		LED-3/13W/2700K	628.5 lm	13 W	80
114-9087		LED-3/13W/3000K	664.7 lm	13 W	80
114-9088_us		LED-3/13W/4000K	694.9 lm	13 W	80