



#### Description

Trilight column. IP44. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses.

Integral EC electronic converter. CAD-optimized lens for superior illumination and glare control.

Service door with fused cable connecting box.

Planted root available on request.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Lens	Prismatic polycarbonate lenses			
Colours	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>
	Signal black	Traffic white	Anthracite grey	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS hardware			
Ingress protection	IP44			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	6/6 kV
Energy efficiency	B-C (Light source)

### Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

**Options**

**Light distribution**    **Colour temperature**    **Nominal Watt**

[]



3000K

37 W



4000K

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	116-0208	LED-1/37W/3000K	2546.5 lm	37 W	80
	116-0209	LED-1/37W/4000K	2656.2 lm	37 W	80