

**Description**

IP66. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate outer lens. Service door with fused cable connecting box. CAD-optimized indirect optics for superior illumination and glare control. 0-10V Dimming comes standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Luminaire head, base plate and base plate cover constructed in die cast aluminum			
Lens	Clear polycarbonate lens.			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] LED driver in 120-277V
Driver / Ballast	Integral EC electronic converter
Surge protection	10/10kV
Energy efficiency	B-C (Light source)

### Additional information

Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L70B50 > 50000h

**Options**

**Light distribution**



[C60] symmetric distribution



[C50] Type V Short

**Color temperature**



3000K



4000K



2700K



**Nominal Watt**

17 W

24 W

37 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C50] Type V Short</p>	115-1778	LED-1/17W/2700K	2397.8 lm	17 W	80
	115-1521_us	LED-1/17W/3000K	2508.1 lm	17 W	80
	115-1522_us	LED-1/17W/4000K	2614.3 lm	17 W	80
	115-1779	LED-1/24W/2700K	3308.7 lm	24 W	80
	115-1523_us	LED-1/24W/3000K	3210.6 lm	24 W	80
	115-1837	LED-1/37W/2700K	5020.2 lm	37 W	80
	115-1565	LED-1/37W/3000K	5171.3 lm	37 W	80
	115-1566	LED-1/37W/4000K	5469.5 lm	37 W	80
 <p>[C60] symmetric distribution</p>	115-1780	LED-1/17W/2700K	1980.1 lm	17 W	80
	115-1517_us	LED-1/17W/3000K	2071.2 lm	17 W	80
	115-1518_us	LED-1/17W/4000K	2158.9 lm	17 W	80
	115-1781	LED-1/24W/2700K	2732.3 lm	24 W	80
	115-1519_us	LED-1/24W/3000K	2651.3 lm	24 W	80
	115-1520_us	LED-1/24W/4000K	2766 lm	24 W	80
	115-1838	LED-1/37W/2700K	4145.7 lm	37 W	80