





Description

Trilight column. IP44. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses.

Integral EC electronic converter. CAD-optimized lens for superior illumination and glare control.

Service door with fused cable connecting box.

Planted root available on request.

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	Prismatic polycarbonate lenses, 3 x 120° offset			
Colours	RAL9004 Signal black	RAL9016 Traffic white	RAL7016 Anthracite grey	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS hardware			
Ingress protection	IP44			
Impact resistance	IK10			
Corrosion resistance	5CE			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Energy efficiency	B-C (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution **Colour temperature** **Nominal Watt**

[]



3000K

37 W



4000K

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
□	116-0207	LED-1/37W/3000K	2546.5 lm	37 W	80
	116-0205	LED-1/37W/4000K	2656.2 lm	37 W	80