

Description

IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

For 2200 K version available on request.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	10/10kV
Energy efficiency	E-F-D (Light source)

Additional information

Options

Light distribution



[C70] symmetric



[S60] asymmetric, side throw


Colour temperature



2700K



3000K





4000K

Nominal Watt

11 W

15 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C70] symmetric	115-9759	LED-1/11W/2700K	844.7 lm	11 W	80
	115-9760	LED-1/11W/3000K	890.7 lm	11 W	80
	115-9761	LED-1/11W/4000K	948.1 lm	11 W	80
	115-9763	LED-1/15W/2700K	1167.8 lm	15 W	80
	115-9764	LED-1/15W/3000K	1182.5 lm	15 W	80
	115-9765	LED-1/15W/4000K	1262.9 lm	15 W	80
 [S60] asymmetric, side throw	115-9789	LED-1/11W/2700K	843.6 lm	11 W	80
	115-9790	LED-1/11W/3000K	889.5 lm	11 W	80
	115-9791	LED-1/11W/4000K	946.9 lm	11 W	80
	115-9793	LED-1/15W/2700K	1166.3 lm	15 W	80
	115-9794	LED-1/15W/3000K	1180.9 lm	15 W	80
	115-9795	LED-1/15W/4000K	1261.3 lm	15 W	80