

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features anodized aluminum core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens, UV-stabilized. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. Luminaire is factory-sealed and does not need to be opened during installation.

Suitable for areas prone to flooding.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter, DALI
Surge protection	10/10kV
Energy efficiency	E-F-D (Light source)

Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
----------	------------------------------------------------------------

Options

Light distribution



[C70] Symmetric Type V



[S60] Type III Short

Color temperature

Nominal Watt



2700K

11 W

15 W





3000K



4000K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [C70] Symmetric Type V	115-9751_us	LED-1/11W/2700K	844.7 lm	11 W	80
	115-9752_us	LED-1/11W/3000K	890.7 lm	11 W	80
	115-9753_us	LED-1/11W/4000K	948.1 lm	11 W	80
	115-9755_us	LED-1/15W/2700K	1167.8 lm	15 W	80
	115-9756_us	LED-1/15W/3000K	1182.5 lm	15 W	80
	115-9757_us	LED-1/15W/4000K	1262.9 lm	15 W	80
	 [S60] Type III Short	115-9781_us	LED-1/11W/2700K	843.6 lm	11 W
115-9782_us		LED-1/11W/3000K	889.5 lm	11 W	80
115-9783_us		LED-1/11W/4000K	946.9 lm	11 W	80
115-9785_us		LED-1/15W/2700K	1166.3 lm	15 W	80
115-9786_us		LED-1/15W/3000K	1180.9 lm	15 W	80
115-9787_us		LED-1/15W/4000K	1261.3 lm	15 W	80