

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features anodized aluminum core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens, UV-stabilized. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. Luminaire is factory-sealed and does not need to be opened during installation.

Suitable for areas prone to flooding.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter, DALI
Surge protection	10/10kV
Energy efficiency	E-F-D (Light source)

Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
----------	--

Options

Light distribution



[C70] Symmetric Type V



[S60] Type III Short

Color temperature



2700K



3000K





4000K

Nominal Watt

11 W

15 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [C70] Symmetric Type V	115-9771_us	LED-1/11W/2700K	844.7 lm	11 W	80
	115-9772_us	LED-1/11W/3000K	890.7 lm	11 W	80
	115-9773_us	LED-1/11W/4000K	948.1 lm	11 W	80
	115-9775_us	LED-1/15W/2700K	1167.8 lm	15 W	80
	115-9776	LED-1/15W/3000K	1182.5 lm	15 W	80
	115-9777	LED-1/15W/4000K	1262.9 lm	15 W	80
	 [S60] Type III Short	115-9801	LED-1/11W/2700K	843.6 lm	11 W
115-9802		LED-1/11W/3000K	889.5 lm	11 W	80
115-9803		LED-1/11W/4000K	946.9 lm	11 W	80
115-9805		LED-1/15W/2700K	1166.3 lm	15 W	80
115-9806		LED-1/15W/3000K	1180.9 lm	15 W	80
115-9807		LED-1/15W/4000K	1261.3 lm	15 W	80