

Description

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF

Specifications

Material description

| | | | | |
|--------------------|-----------------|----------------|-----------------|----------------|
| Colours | RAL9004 | RAL9007 | RAL7016 | RAL9016 |
| | Signal black | Grey aluminium | Anthracite grey | Traffic white |
| | RAL9006 | | | |
| | White aluminium | | | |
| Ingress protection | IP66 | | | |
| Impact resistance | IK10 | | | |


Electrical description


| | |
|-------------------|----------------------------------------|
| Driver / Ballast | Integral EC electronic converter, DALI |
| Surge protection | 10/10kV |
| Energy efficiency | F (Light source) |

Additional information

Options

Light distribution

 [C70] symmetric

 [S60] asymmetric, side throw



Colour temperature

2700-5000K

Nominal Watt

10 W

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|------------------------------------------------------------------------------------------------------------------|----------|----------------------|--------------|-------------------|-----|
|  [C70] symmetric | 115-9812 | LED-1/10W/2700-5000K | 699.9 lm | 10 W | 80 |
|  [S60] asymmetric, side throw | 115-9815 | LED-1/10W/2700-5000K | 567.2 lm | 10 W | 80 |