

**Description**

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9006</b> White aluminium
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

---

### Electrical description

---

Driver / Ballast	Integral EC electronic converter, DALI		
Surge protection	10/10kV		
Energy efficiency	F (Light source)		

---

### Additional information

**Options**

**Light distribution**

**Colour temperature**

**Nominal Watt**



[C70] symmetric



2700-5000K

10 W



[S60] asymmetric, side throw

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C70] symmetric	115-9812	LED-1/10W/2700-5000K	699.9 lm	10 W	80
 [S60] asymmetric, side throw	115-9815	LED-1/10W/2700-5000K	567.2 lm	10 W	80