

### Description

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL7016</b>	<b>RAL9016</b>	<b>RAL9007</b>
	Signal black	Anthracite grey	Traffic white	Grey aluminium
	<b>RAL9006</b>			
	White aluminium			
Ingress protection	IP66			
Impact resistance	IK10			

### Electrical description

Surge protection	10/10kV
Energy efficiency	F (Light source)

### Additional information

Lifetime	Ta=25° L70B50>50000h
----------	----------------------

## Options

### Light distribution



[C70] symmetric



[S60] asymmetric, side throw



### Colour temperature

2700-5000K

### Nominal Watt

10 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C70] symmetric	115-9811	LED-1/10W/2700-5000K	699.9 lm	10 W	80
 [S60] asymmetric, side throw	115-9814	LED-1/10W/2700-5000K	567.2 lm	10 W	80