



Description

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Specifications

Material description

| | | | | |
|--------------------|--------------------------------|---------------------------------|----------------------------------|------------------------------|
| Colors | RAL9004 Signal black | RAL9016 Traffic white | RAL9007 Grey aluminium | RAL8019 Grey brown |
| Ingress protection | IP66 | | | |
| Impact resistance | IK10 | | | |

Electrical description

| | |
|-------------------|------------------|
| Surge protection | 10/10kV |
| Energy efficiency | F (Light source) |

Additional information

| | |
|----------|----------------------|
| Lifetime | Ta=25° L70B50>50000h |
|----------|----------------------|

Options

Light distribution Color temperature Nominal Watt

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI |
|--------------------|---------|--------------|------------------|-------------------|-----|
|--------------------|---------|--------------|------------------|-------------------|-----|
