



### Description

Tunable white. IP66. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features anodised aluminium core. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens, UV-stabilised. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

**Specifications**

**Material description**

Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL9007</b> Grey aluminium	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK10			

**Electrical description**

Surge protection	10/10kV
Energy efficiency	F (Light source)

**Additional information**

Height (inches)	
Lifetime	Ta=25° L70B50>50000h

---

**Options**

Light distribution    Color temperature    Nominal Watt

### Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
--------------------	---------	--------------	------------------	-------------------	-----