

Description

IP65, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 1-10V or DALI interface on request. Optional 2200 K version available. To be specified at time of ordering.

Can be mounted up or down.

Specifications

Material description

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens

Colours

RAL9004	RAL9006	RAL9016	RAL7016
Signal black	White aluminium	Traffic white	Anthracite grey
RAL9007			
Grey aluminium			

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP65

Impact resistance IK07

Corrosion resistance 5CE

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Standard. Optional DALI version available. To be specified at time of ordering.

Surge protection 1/2 kV (optional SP10)

Energy efficiency C-D (Light source)

Additional information

Lifetime Ta=25° L90B10 > 90000h

Options

Light distribution



[S70] asymmetric, side throw



[R65] rectangular, side throw




[A60] asymmetric, forward throw

Colour temperature



3000K



4000K






2700K

Nominal Watt

12 W

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[A60] asymmetric, forward throw</p>	132-0641	LED-12/12W/2700K	1381 lm	12 W	80
	132-0530	LED-12/12W/3000K	1476.3 lm	12 W	80
	132-0531	LED-12/12W/4000K	1619.1 lm	12 W	80
	132-0642	LED-12/24W/2700K	2449.2 lm	24 W	80
	132-0540	LED-12/24W/3000K	2630.6 lm	24 W	80
	132-0541	LED-12/24W/4000K	2812 lm	24 W	80
 <p>[R65] rectangular, side throw</p>	132-0639	LED-12/12W/2700K	1304.5 lm	12 W	80
	132-0528	LED-12/12W/3000K	1394.4 lm	12 W	80
	132-0529	LED-12/12W/4000K	1529.4 lm	12 W	80
	132-0640	LED-12/24W/2700K	2313.3 lm	24 W	80
	132-0538	LED-12/24W/3000K	2484.7 lm	24 W	80
	132-0539	LED-12/24W/4000K	2656.1 lm	24 W	80
 <p>[S70] asymmetric, side throw</p>	132-0637	LED-12/12W/2700K	1449.3 lm	12 W	80
	132-0526	LED-12/12W/3000K	1549.2 lm	12 W	80
	132-0527	LED-12/12W/4000K	1699.2 lm	12 W	80
	132-0638	LED-12/24W/2700K	2570.2 lm	24 W	80
	132-0536	LED-12/24W/3000K	2760.6 lm	24 W	80
	132-0537	LED-12/24W/4000K	2951 lm	24 W	80