

Description

IP65, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 1-10V or DALI interface on request. Optional 2200 K version available. To be specified at time of ordering.

Can be mounted up or down.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP65			
Impact resistance	IK07			
Corrosion resistance	5CE			

Electrical description


Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	1/2 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information


Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options


Light distribution


 [S70] asymmetric, side throw

 [R65]

 [A60] asymmetric, forward throw

Colour temperature

 3000K

 4000K




 2700K

Nominal Watt

12 W

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[A60] asymmetric, forward throw</p>	132-0641	LED-12/12W/2700K	1381 lm	12 W	80
	132-0530	LED-12/12W/3000K	1476.3 lm	12 W	80
	132-0531	LED-12/12W/4000K	1619.1 lm	12 W	80
	132-0642	LED-12/24W/2700K	2449.2 lm	24 W	80
	132-0540	LED-12/24W/3000K	2630.6 lm	24 W	80
	132-0541	LED-12/24W/4000K	2812 lm	24 W	80
 <p>[R65]</p>	132-0639	LED-12/12W/2700K	1304.5 lm	12 W	80
	132-0528	LED-12/12W/3000K	1394.4 lm	12 W	80
	132-0529	LED-12/12W/4000K	1529.4 lm	12 W	80
	132-0640	LED-12/24W/2700K	2313.3 lm	24 W	80
	132-0538	LED-12/24W/3000K	2484.7 lm	24 W	80
	132-0539	LED-12/24W/4000K	2656.1 lm	24 W	80
 <p>[S70] asymmetric, side throw</p>	132-0637	LED-12/12W/2700K	1449.3 lm	12 W	80
	132-0526	LED-12/12W/3000K	1549.2 lm	12 W	80
	132-0527	LED-12/12W/4000K	1699.2 lm	12 W	80
	132-0638	LED-12/24W/2700K	2570.2 lm	24 W	80
	132-0536	LED-12/24W/3000K	2760.6 lm	24 W	80
	132-0537	LED-12/24W/4000K	2951 lm	24 W	80