

#### Description

IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass, hinged. Integral EC electronic converter. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Luminaire +/-30° tiltable.

## Specifications

### Material description

---

Body	Marine-grade, die-cast aluminium alloy						
Lens	Safety glass lens, hinged						
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9006</b></td><td><b>RAL9007</b></td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	Signal black	White aluminium	Grey aluminium
<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>					
Signal black	White aluminium	Grey aluminium					
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP66						
Impact resistance	IK08						
Corrosion resistance	5CE+Primer						

---

### Electrical description

---

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.




---

### Additional information

---

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------




---

**Options****Light distribution** [S65] asymmetric, side throw [R65] rectangular, side throw [A60] asymmetric, forward throw**Colour temperature** 3000K 4000K 2700K**Nominal Watt**

24 W

36 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [A60] asymmetric, forward throw	108-2537	LED-12/24W/2700K	2426.7 lm	24 W	80
	108-1666	LED-12/24W/3000K	2606.4 lm	24 W	80
	108-1667	LED-12/24W/4000K	2786.2 lm	24 W	80
	108-2538	LED-18/36W/2700K	3640 lm	36 W	80
	108-1751	LED-18/36W/3000K	3909.6 lm	36 W	80
	108-1752	LED-18/36W/4000K	4179.3 lm	36 W	80
 [R65] rectangular, side throw	108-2539	LED-12/24W/2700K	2266.5 lm	24 W	80
	108-1664	LED-12/24W/3000K	2434.4 lm	24 W	80
	108-1665	LED-12/24W/4000K	2602.3 lm	24 W	80
	108-2540	LED-18/36W/2700K	3399.8 lm	36 W	80
	108-1749	LED-18/36W/3000K	3651.7 lm	36 W	80
	108-1750	LED-18/36W/4000K	3903.5 lm	36 W	80
 [S65] asymmetric, side throw	108-2535	LED-12/24W/2700K	2588.6 lm	24 W	80
	108-1660	LED-12/24W/3000K	2780.3 lm	24 W	80
	108-1661	LED-12/24W/4000K	2972.1 lm	24 W	80
	108-2536	LED-18/36W/2700K	3882.9 lm	36 W	80
	108-1747	LED-18/36W/3000K	4170.5 lm	36 W	80
	108-1748	LED-18/36W/4000K	4458.1 lm	36 W	80