

Description

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Luminaire can be mounted for up or down lighting.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

Additional information

Width x Depth (inches)	10.43 x 8.86
Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options


Light distribution




[M]



[E]



[S70] Type II Short



[A60] Type IV Very Short



[R65]

Color temperature



3000K



4000K



2700K





Nominal Watt


12 W

18 W

26 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	131-9626	LED-6/12W/2700K	940.2 lm	12 W	80
	131-9575	LED-6/12W/3000K	1009.9 lm	12 W	80
	131-9576	LED-6/12W/4000K	1079.5 lm	12 W	80
	131-9627	LED-6/18W/2700K	1348.1 lm	18 W	80
	131-9577	LED-6/18W/3000K	1413.8 lm	18 W	80
	131-9578	LED-6/18W/4000K	1479.6 lm	18 W	80
	131-9628	LED-6/26W/2700K	1709.7 lm	26 W	80
	131-9579	LED-6/26W/3000K	1808.4 lm	26 W	80
	131-9580	LED-6/26W/4000K	1890.6 lm	26 W	80
 <p>[E]</p>	131-9632	LED-6/12W/2700K	1223.2 lm	12 W	80
	131-9587	LED-6/12W/3000K	1313.8 lm	12 W	80
	131-9588	LED-6/12W/4000K	1404.4 lm	12 W	80
	131-9633	LED-6/18W/2700K	1972.3 lm	18 W	80
	131-9589	LED-6/18W/3000K	2068.5 lm	18 W	80
	131-9590	LED-6/18W/4000K	2164.7 lm	18 W	80
	131-9634	LED-6/26W/2700K	2501.5 lm	26 W	80
	131-9591	LED-6/26W/3000K	2645.8 lm	26 W	80
	131-9592	LED-6/26W/4000K	2766.1 lm	26 W	80
 <p>[M]</p>	131-9629	LED-6/12W/2700K	1300.7 lm	12 W	80
	131-9581	LED-6/12W/3000K	1397.1 lm	12 W	80
	131-9582	LED-6/12W/4000K	1493.4 lm	12 W	80
	131-9630	LED-6/18W/2700K	1944.8 lm	18 W	80
	131-9583	LED-6/18W/3000K	2039.7 lm	18 W	80
	131-9584	LED-6/18W/4000K	2134.6 lm	18 W	80
	131-9631	LED-6/26W/2700K	2466.6 lm	26 W	80
	131-9585	LED-6/26W/3000K	2608.9 lm	26 W	80
	131-9586	LED-6/26W/4000K	2727.5 lm	26 W	80
 <p>[R65]</p>	131-9623	LED-6/12W/2700K	880.1 lm	12 W	80
	131-9569	LED-6/12W/3000K	945.3 lm	12 W	80
	131-9570	LED-6/12W/4000K	1010.5 lm	12 W	80
	131-9624	LED-6/18W/2700K	1311 lm	18 W	80
	131-9571	LED-6/18W/3000K	1374.9 lm	18 W	80

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[S70] Type II Short</p>	131-9572	LED-6/18W/4000K	1438.9 lm	18 W	80
	131-9625	LED-6/26W/2700K	1662.7 lm	26 W	80
	131-9573	LED-6/26W/3000K	1758.6 lm	26 W	80
	131-9574	LED-6/26W/4000K	1838.6 lm	26 W	80
	131-9620	LED-6/12W/2700K	968.2 lm	12 W	80
	131-9562	LED-6/12W/3000K	1039.9 lm	12 W	80
	131-9564	LED-6/12W/4000K	1111.6 lm	12 W	80
	131-9621	LED-6/18W/2700K	1430.2 lm	18 W	80
	131-9565	LED-6/18W/3000K	1499.9 lm	18 W	80
	131-9566	LED-6/18W/4000K	1569.7 lm	18 W	80
	131-9622	LED-6/26W/2700K	1813.9 lm	26 W	80
	131-9567	LED-6/26W/3000K	1918.5 lm	26 W	80
	131-9568	LED-6/26W/4000K	2005.7 lm	26 W	80