

Description

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. CAD-optimized optics for superior illumination and glare control. Integral driver. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Luminaire can be mounted for up or down lighting.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description


Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)


Additional information


Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h


Options


Light distribution

 [M] symmetric, medium beam

 [N] bi-symmetric, narrow beam
[]

 [S70] Type II Short

 [A60] Type IV Very Short

 [R65] Type IV Medium

Color temperature

 3000K

 4000K

 2700K






Nominal Watt


12 W

18 W

26 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
	131-9591_us	LED-6/26W/3000K	2645.8 lm	26 W	80	
 [A60] Type IV Very Short	131-9626_us	LED-6/12W/2700K	940.2 lm	12 W	80	
	131-9575_us	LED-6/12W/3000K	1009.9 lm	12 W	80	
	131-9576_us	LED-6/12W/4000K	1079.5 lm	12 W	80	
	131-9627_us	LED-6/18W/2700K	1348.1 lm	18 W	80	
	131-9577_us	LED-6/18W/3000K	1413.8 lm	18 W	80	
	131-9578_us	LED-6/18W/4000K	1479.6 lm	18 W	80	
	131-9628_us	LED-6/26W/2700K	1709.7 lm	26 W	80	
	131-9579_us	LED-6/26W/3000K	1808.4 lm	26 W	80	
	131-9580_us	LED-6/26W/4000K	1890.6 lm	26 W	80	
	 [M] symmetric, medium beam	131-9629_us	LED-6/12W/2700K	1300.7 lm	12 W	80
131-9581_us		LED-6/12W/3000K	1397.1 lm	12 W	80	
131-9582_us		LED-6/12W/4000K	1493.4 lm	12 W	80	
131-9630_us		LED-6/18W/2700K	1944.8 lm	18 W	80	
131-9583_us		LED-6/18W/3000K	2039.7 lm	18 W	80	
131-9584_us		LED-6/18W/4000K	2134.6 lm	18 W	80	
131-9631_us		LED-6/26W/2700K	2466.6 lm	26 W	80	
131-9585_us		LED-6/26W/3000K	2608.9 lm	26 W	80	
131-9586_us		LED-6/26W/4000K	2727.5 lm	26 W	80	
 [N] bi-symmetric, narrow beam		131-9632_us	LED-6/12W/2700K	1223.2 lm	12 W	80
	131-9587_us	LED-6/12W/3000K	1313.8 lm	12 W	80	
	131-9588_us	LED-6/12W/4000K	1404.4 lm	12 W	80	
	131-9633_us	LED-6/18W/2700K	1972.3 lm	18 W	80	
	131-9589_us	LED-6/18W/3000K	2068.5 lm	18 W	80	
	131-9590_us	LED-6/18W/4000K	2164.7 lm	18 W	80	
	131-9634_us	LED-6/26W/2700K	2501.5 lm	26 W	80	
	131-9592_us	LED-6/26W/4000K	2766.1 lm	26 W	80	
	 [R65] Type IV Medium	131-9623_us	LED-6/12W/2700K	880.1 lm	12 W	80
		131-9569_us	LED-6/12W/3000K	945.3 lm	12 W	80
131-9570_us		LED-6/12W/4000K	1010.5 lm	12 W	80	
131-9624_us		LED-6/18W/2700K	1311 lm	18 W	80	
131-9571_us		LED-6/18W/3000K	1374.9 lm	18 W	80	

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[S70] Type II Short</p>	131-9572_us	LED-6/18W/4000K	1438.9 lm	18 W	80
	131-9625_us	LED-6/26W/2700K	1662.7 lm	26 W	80
	131-9573_us	LED-6/26W/3000K	1758.6 lm	26 W	80
	131-9574_us	LED-6/26W/4000K	1838.6 lm	26 W	80
	131-9620_us	LED-6/12W/2700K	968.2 lm	12 W	80
	131-9562_us	LED-6/12W/3000K	1039.9 lm	12 W	80
	131-9564_us	LED-6/12W/4000K	1111.6 lm	12 W	80
	131-9621_us	LED-6/18W/2700K	1430.2 lm	18 W	80
	131-9565_us	LED-6/18W/3000K	1499.9 lm	18 W	80
	131-9566_us	LED-6/18W/4000K	1569.7 lm	18 W	80
	131-9622_us	LED-6/26W/2700K	1813.9 lm	26 W	80
	131-9567_us	LED-6/26W/3000K	1918.5 lm	26 W	80
	131-9568_us	LED-6/26W/4000K	2005.7 lm	26 W	80