

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features galvanized steel reinforcement core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with 10kV surge protector in cable connection box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy. Inner steel core.			
Lens	RFC® Reflection Free Contour main lens			
Colors	RAL9004	RAL9007	RAL9016	RAL8019
	Signal black	Grey aluminium	Traffic white	Grey brown
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DALI
Surge protection	Integral 10kV Surge Protector
Energy efficiency	Energy efficiency class

Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution



[R45] rectangular asymmetric Type II

Color temperature

Nominal Watt



3000K

6 W

9 W




4000K

13 W



2700K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[R45] rectangular asymmetric Type II</p>	114-0184	LED-3/6W/2700K	606 lm	6 W	80
	114-0128_us	LED-3/6W/3000K	650.8 lm	6 W	80
	114-0129_us	LED-3/6W/4000K	695.7 lm	6 W	80
	114-0185	LED-3/9W/2700K	909.1 lm	9 W	80
	114-0130_us	LED-3/9W/3000K	953.5 lm	9 W	80
	114-0131_us	LED-3/9W/4000K	997.8 lm	9 W	80
	114-0186	LED-3/13W/2700K	1153 lm	13 W	80
	114-0132_us	LED-3/13W/3000K	1219.5 lm	13 W	80
	114-0133_us	LED-3/13W/4000K	1275 lm	13 W	80