

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features galvanized steel reinforcement core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with 10kV surge protector in cable connection box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy. Inner steel core.			
Lens	RFC® Reflection Free Contour main lens			
Colors	RAL9004	RAL9007	RAL9016	RAL8019
	Signal black	Grey aluminium	Traffic white	Grey brown
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			





Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DALI
Surge protection	Integral 10kV Surge Protector
Energy efficiency	Energy efficiency class


Additional information

Height (inches)	31.50
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [R45]	 3000K	6 W
	 4000K	9 W
	 2700K	13 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[R45]</p>	114-0184	LED-3/6W/2700K	606 lm	6 W	80
	114-0128	LED-3/6W/3000K	650.8 lm	6 W	80
	114-0129	LED-3/6W/4000K	695.7 lm	6 W	80
	114-0185	LED-3/9W/2700K	909.1 lm	9 W	80
	114-0130	LED-3/9W/3000K	953.5 lm	9 W	80
	114-0131	LED-3/9W/4000K	997.8 lm	9 W	80
	114-0186	LED-3/13W/2700K	1153 lm	13 W	80
	114-0132	LED-3/13W/3000K	1219.5 lm	13 W	80
	114-0133	LED-3/13W/4000K	1275 lm	13 W	80