

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features galvanized steel reinforcement core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with 10kV surge protector in cable connection box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

For DarkSky compliant configurations of this product, please find the spec sheet and DarkSky certificate in the library.

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DALI
Surge protection	10kV (SP10)
Energy efficiency	C-D (Light source)

Additional information

Listings	ETL Listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution

Color temperature

Nominal Watt



[S70] Type II Short



3000K

12 W

18 W

26 W



[A60] Type IV Very Short



4000K






[R65] Type IV Medium



2700K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	114-0190	LED-6/12W/2700K	1325.7 lm	12 W	80
	114-9701	LED-6/12W/3000K	1423.9 lm	12 W	80
	114-9702	LED-6/12W/4000K	1522.1 lm	12 W	80
	114-0191	LED-6/18W/2700K	1847.6 lm	18 W	80
	114-9703	LED-6/18W/3000K	1937.7 lm	18 W	80
	114-9704	LED-6/18W/4000K	2027.8 lm	18 W	80
	114-0192	LED-6/26W/2700K	2343.3 lm	26 W	80
	114-9705	LED-6/26W/3000K	2478.5 lm	26 W	80
	114-9706	LED-6/26W/4000K	2591.1 lm	26 W	80
 <p>[R65] Type IV Medium</p>	114-0146_us	LED-6/12W/3000K	1229.6 lm	12 W	80
	114-0147_us	LED-6/12W/4000K	1314.4 lm	12 W	80
	114-0194	LED-6/18W/2700K	1820.7 lm	18 W	80
	114-0148_us	LED-6/18W/3000K	1909.5 lm	18 W	80
	114-0149_us	LED-6/18W/4000K	1998.3 lm	18 W	80
	114-0195	LED-6/26W/2700K	2309.2 lm	26 W	80
	114-0150_us	LED-6/26W/3000K	2442.4 lm	26 W	80
	114-0151_us	LED-6/26W/4000K	2553.4 lm	26 W	80
 <p>[S70] Type II Short</p>	114-0187	LED-6/12W/2700K	1273.5 lm	12 W	80
	114-0134_us	LED-6/12W/3000K	1367.8 lm	12 W	80
	114-0135_us	LED-6/12W/4000K	1462.2 lm	12 W	80
	114-0188	LED-6/18W/2700K	2038.1 lm	18 W	80
	114-0136_us	LED-6/18W/3000K	2137.5 lm	18 W	80
	114-0137_us	LED-6/18W/4000K	2237 lm	18 W	80
	114-0189	LED-6/26W/2700K	2584.9 lm	26 W	80
	114-0138_us	LED-6/26W/3000K	2734.1 lm	26 W	80
	114-0139_us	LED-6/26W/4000K	2858.3 lm	26 W	80