

### Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. Pole section features galvanized steel reinforcement core. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with 10kV surge protector in cable connection box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

For DarkSky compliant configurations of this product, please find the spec sheet and DarkSky certificate in the library.

## Specifications

### Material description

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK10			







### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	DALI
Surge protection	10kV (SP10)
Energy efficiency	C-D (Light source)




### Additional information

Height (inches)	39.37
Listings	ETL Listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

Light distribution	Color temperature	Nominal Watt
 [S70] Type II Short	 3000K	12 W 18 W
 [A60] Type IV Very Short	 4000K	26 W
 [R65]	 2700K	

### Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	114-0190	LED-6/12W/2700K	1325.7 lm	12 W	80
	114-9701	LED-6/12W/3000K	1423.9 lm	12 W	80
	114-9702	LED-6/12W/4000K	1522.1 lm	12 W	80
	114-0191	LED-6/18W/2700K	1847.6 lm	18 W	80
	114-9703	LED-6/18W/3000K	1937.7 lm	18 W	80
	114-9704	LED-6/18W/4000K	2027.8 lm	18 W	80
	114-0192	LED-6/26W/2700K	2343.3 lm	26 W	80
	114-9705	LED-6/26W/3000K	2478.5 lm	26 W	80
	114-9706	LED-6/26W/4000K	2591.1 lm	26 W	80
 <p>[R65]</p>	114-0146	LED-6/12W/3000K	1229.6 lm	12 W	80
	114-0147	LED-6/12W/4000K	1314.4 lm	12 W	80
	114-0194	LED-6/18W/2700K	1820.7 lm	18 W	80
	114-0148	LED-6/18W/3000K	1909.5 lm	18 W	80
	114-0149	LED-6/18W/4000K	1998.3 lm	18 W	80
	114-0195	LED-6/26W/2700K	2309.2 lm	26 W	80
	114-0150	LED-6/26W/3000K	2442.4 lm	26 W	80
	114-0151	LED-6/26W/4000K	2553.4 lm	26 W	80
	 <p>[S70] Type II Short</p>	114-0187	LED-6/12W/2700K	1273.5 lm	12 W
114-0134		LED-6/12W/3000K	1367.8 lm	12 W	80
114-0135		LED-6/12W/4000K	1462.2 lm	12 W	80
114-0188		LED-6/18W/2700K	2038.1 lm	18 W	80
114-0136		LED-6/18W/3000K	2137.5 lm	18 W	80
114-0137		LED-6/18W/4000K	2237 lm	18 W	80
114-0189		LED-6/26W/2700K	2584.9 lm	26 W	80
114-0138		LED-6/26W/3000K	2734.1 lm	26 W	80
114-0139		LED-6/26W/4000K	2858.3 lm	26 W	80