

Description

IP66/IP67. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features galvanised steel reinforcement core. 5CE superior corrosion protection + primer including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Specifications

Material description

Colours

RAL9004

Signal black

RAL9007

Grey aluminium

RAL9006

White aluminium

Ingress protection IP67

Impact resistance IK10

Corrosion resistance 5CE+Primer

Electrical description

Additional information

Lifetime Ta=40° L90B10 > 90000h

Options

Light distribution



[R45/R45] rectangular, side throw

Colour temperature



2700K



3000K



4000K


Nominal Watt

12 W

18 W

26 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R45/R45] rectangular, side throw	114-9751	LED-3/12W/2700K	1204 lm	12 W	80
	114-9752	LED-6/12W/3000K	1293.2 lm	12 W	80
	114-9753	LED-6/12W/4000K	1382.3 lm	12 W	80
	114-9754	LED-3/18W/2700K	1806.8 lm	18 W	80
	114-9755	LED-6/18W/3000K	1894.9 lm	18 W	80
	114-9756	LED-6/18W/4000K	1983.1 lm	18 W	80
	114-9757	LED-3/26W/2700K	2291.6 lm	26 W	80
	114-9758	LED-6/26W/3000K	2423.8 lm	26 W	80
	114-9759	LED-6/26W/4000K	2533.9 lm	26 W	80