

Description

IP66/IP67. Class I. IK10. Marine-grade, all-aluminium construction. Pole section features galvanised steel reinforcement core. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Specifications

Material description





Lens	RFC™ Reflection Free Contour main lens			
Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP67			
Impact resistance	IK10			

Electrical description


Driver / Ballast	Integral EC electronic converter
Surge protection	6/6 kV (SP10 optional)

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
 [R45/R45]	 2700K	12 W
	 3000K	18 W
	 4000K	26 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R45/R45]	114-9751	LED-3/12W/2700K	1204 lm	12 W	80
	114-9752	LED-6/12W/3000K	1293.2 lm	12 W	80
	114-9753	LED-6/12W/4000K	1382.3 lm	12 W	80
	114-9754	LED-3/18W/2700K	1806.8 lm	18 W	80
	114-9755	LED-6/18W/3000K	1894.9 lm	18 W	80
	114-9756	LED-6/18W/4000K	1983.1 lm	18 W	80
	114-9757	LED-3/26W/2700K	2291.6 lm	26 W	80
	114-9758	LED-6/26W/3000K	2423.8 lm	26 W	80
	114-9759	LED-6/26W/4000K	2533.9 lm	26 W	80