

**Description**

IP66, Class I, IK07. Surface mounted LED wall luminaire. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral driver. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming on request. Suitable for installation over 4" recessed junction box. Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.

ADA (American Disabilities Act) Compliant.

For DarkSky compliant configurations of this product, please find the spec sheet and DarkSky certificate in the library.

## Specifications

### Material description

Body	Luminaire body and lens frame constructed in die cast aluminum.			
Lens	Clear tempered glass lens.			
Colors	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL8019</b>	<b>RAL9007</b>
	Signal black	Traffic white	Grey brown	Grey aluminium
Fasteners	PCS polymer coated stainless steel			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			
















### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)





### Additional information





Height x Depth (inches)	9.06 x 3.74
Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h





**Options**

Light distribution	Color temperature	Nominal Watt
 [M]	 3000K	12 W
		24 W
 [M/M]	 4000K	18 W
		36 W
 [S]	 2700K	26 W
 [M/S]		52 W
 [E/S]		
 [E]		
 [E/E]		
 [R45]		
 [M/R45]		
 [E/R45]		
 [E/M]		
 [R45/R45]		

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[E]</p>	131-9428	LED-6/12W/2700K	1223.2 lm	12 W	80
	131-9460	LED-6/12W/3000K	1313.8 lm	12 W	80
	131-9461	LED-6/12W/4000K	1404.4 lm	12 W	80
	131-9887	LED-6/18W/2700K	1857.4 lm	18 W	80
	131-0188	LED-6/18W/3000K	1948 lm	18 W	80
	131-0189	LED-6/18W/4000K	2038.6 lm	18 W	80
	131-9889	LED-6/26W/2700K	2355.8 lm	26 W	80
	131-0194	LED-6/26W/3000K	2491.7 lm	26 W	80
	131-0195	LED-6/26W/4000K	2604.9 lm	26 W	80
 <p>[E/E]</p>	131-9433	LED-6/24W/2700K	2447.1 lm	24 W	80
	131-9453	LED-6/24W/3000K	2628.4 lm	24 W	80
	131-9454	LED-6/24W/4000K	2809.6 lm	24 W	80
	131-9894	LED-6/36W/2700K	3716 lm	36 W	80
	131-9758	LED-6/36W/3000K	3897.2 lm	36 W	80
	131-9763	LED-6/36W/4000K	4078.5 lm	36 W	80
	131-9903	LED-6/52W/2700K	4712.9 lm	52 W	80
	131-9768	LED-6/52W/3000K	4984.8 lm	52 W	80
	131-9773	LED-6/52W/4000K	5211.4 lm	52 W	80
 <p>[E/M]</p>	131-9432	LED-6/24W/2700K	2315.8 lm	24 W	80
	131-9893	LED-6/36W/2700K	3516.5 lm	36 W	80
	131-9757	LED-6/36W/3000K	3688.1 lm	36 W	80
	131-9762	LED-6/36W/4000K	3859.6 lm	36 W	80
	131-9902	LED-6/52W/2700K	4460 lm	52 W	80
	131-9767	LED-6/52W/3000K	4717.3 lm	52 W	80
	131-9772	LED-6/52W/4000K	4931.7 lm	52 W	80
 <p>[E/R45]</p>	131-9702	LED-6/24W/2700K	2326.4 lm	24 W	80
	131-9464	LED-6/24W/3000K	2498.7 lm	24 W	80
	131-9465	LED-6/24W/4000K	2671 lm	24 W	80
	131-9897	LED-6/36W/2700K	3532.7 lm	36 W	80
	131-9755	LED-6/36W/3000K	3705 lm	36 W	80
	131-9760	LED-6/36W/4000K	3877.3 lm	36 W	80
	131-9906	LED-6/52W/2700K	4480.4 lm	52 W	80

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
 <p>[E/S]</p>	131-9765	LED-6/52W/3000K	4738.9 lm	52 W	80	
	131-9770	LED-6/52W/4000K	4954.3 lm	52 W	80	
	131-9430	LED-6/24W/2700K	2254.7 lm	24 W	80	
	131-9445	LED-6/24W/3000K	2421.7 lm	24 W	80	
	131-9450	LED-6/24W/4000K	2588.7 lm	24 W	80	
	131-7042	LED-6/36W/2700K	3423.7 lm	36 W	80	
 <p>[M]</p>	131-7045	LED-6/52W/2700K	4342.3 lm	52 W	80	
	131-9427	LED-6/12W/2700K	1092 lm	12 W	80	
	131-9438	LED-6/12W/3000K	1172.9 lm	12 W	80	
	131-9441	LED-6/12W/4000K	1253.8 lm	12 W	80	
	131-9886	LED-6/18W/2700K	1658.3 lm	18 W	80	
	131-0186	LED-6/18W/3000K	1739.1 lm	18 W	80	
	131-0187	LED-6/18W/4000K	1820 lm	18 W	80	
	131-9888	LED-6/26W/2700K	2103.2 lm	26 W	80	
	131-0192	LED-6/26W/3000K	2224.5 lm	26 W	80	
	131-0193	LED-6/26W/4000K	2325.6 lm	26 W	80	
	 <p>[M/M]</p>	131-9431	LED-6/24W/2700K	2184.4 lm	24 W	80
		131-9446	LED-6/24W/3000K	2346.2 lm	24 W	80
131-9451		LED-6/24W/4000K	2508.1 lm	24 W	80	
131-9892		LED-6/36W/2700K	3317.1 lm	36 W	80	
131-9756		LED-6/36W/3000K	3478.9 lm	36 W	80	
131-9761		LED-6/36W/4000K	3640.7 lm	36 W	80	
131-9901		LED-6/52W/2700K	4207.1 lm	52 W	80	
131-9766		LED-6/52W/3000K	4449.8 lm	52 W	80	
131-9771		LED-6/52W/4000K	4652 lm	52 W	80	
 <p>[M/R45]</p>		131-9701	LED-6/24W/2700K	2195.1 lm	24 W	80
		131-9456	LED-6/24W/3000K	2357.7 lm	24 W	80
	131-9458	LED-6/24W/4000K	2520.3 lm	24 W	80	
	131-9896	LED-6/36W/2700K	3333.2 lm	36 W	80	
	131-9754	LED-6/36W/3000K	3495.8 lm	36 W	80	
	131-9759	LED-6/36W/4000K	3658.4 lm	36 W	80	
	131-9905	LED-6/52W/2700K	4227.5 lm	52 W	80	
	131-9764	LED-6/52W/3000K	4471.4 lm	52 W	80	

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M/S]</p>	131-9769	LED-6/52W/4000K	4674.7 lm	52 W	80
	131-9429	LED-6/24W/2700K	2123.3 lm	24 W	80
	131-9444	LED-6/24W/3000K	2280.6 lm	24 W	80
	131-9449	LED-6/24W/4000K	2437.9 lm	24 W	80
	131-7036	LED-6/36W/2700K	3224.3 lm	36 W	80
 <p>[R45]</p>	131-7039	LED-6/52W/2700K	4089.4 lm	52 W	80
	131-9700	LED-6/12W/2700K	1102.7 lm	12 W	80
	131-9455	LED-6/12W/3000K	1184.4 lm	12 W	80
	131-9457	LED-6/12W/4000K	1266.1 lm	12 W	80
	131-9895	LED-6/18W/2700K	1674.5 lm	18 W	80
	131-0190	LED-6/18W/3000K	1756.2 lm	18 W	80
	131-0191	LED-6/18W/4000K	1837.9 lm	18 W	80
	131-9904	LED-6/26W/2700K	2123.8 lm	26 W	80
	131-0196	LED-6/26W/3000K	2246.3 lm	26 W	80
	131-0197	LED-6/26W/4000K	2348.4 lm	26 W	80
 <p>[R45/R45]</p>	131-9703	LED-6/24W/2700K	4411 lm	24 W	80
	131-9898	LED-6/36W/2700K	6698.2 lm	36 W	80
	131-9907	LED-6/52W/2700K	8495.3 lm	52 W	80
 <p>[S]</p>	131-9426	LED-6/12W/2700K	1031.3 lm	12 W	80
	131-9437	LED-6/12W/3000K	1107.7 lm	12 W	80
	131-9440	LED-6/12W/4000K	1184.1 lm	12 W	80
	131-7030	LED-6/18W/2700K	1566 lm	18 W	80
	131-7033	LED-6/26W/2700K	1986.2 lm	26 W	80