

Description

Recessed LED wall luminaire.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. 0-10V Dimming comes standard with luminaire.

A pre-installation blackout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Luminaire body and lens frame constructed in die cast aluminum.			
Lens	Tempered glass lens.			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS polymer coated stainless steel			
Ingress protection	IP55			
Impact resistance	IK08			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV

Additional information

Listings	ETL listed. Suitable for wet locations.
Lifetime	LED >60,000 h Ta 25°(B10/70) Control gear >50,000 h Ta 25°

Options

Light distribution



[EC] asymmetric, forward throw

Color temperature

Nominal Watt



3000K

12 W
6 W




4000K



2700K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[EC] asymmetric, forward throw</p>	197-9090_us	LED-2/6W/2700K	376.9 lm	6 W	80
	197-9091_us	LED-2/12W/2700K	473.6 lm	12 W	80
	197-9084_us	LED-2/12W/3000K	511.9 lm	12 W	80
	197-9086_us	LED-2/12W/4000K	531 lm	12 W	80