

Description

The RFL110 features an elegant round shape, designed with the future in mind, offering a full suite of connectivity options. Post top installation on poles, seamlessly blending into urban landscapes by day and night. Constructed from marine-grade, die-cast aluminium alloy, with an IP66 rating, 5CE superior corrosion protection including PCS hardware and CCG® Controlled Compression Gasket. Non-reflective flat safety glass cover, hinged. Integral EC electronic converter, class I or class II. OLC® One LED Concept CAD-optimised optics and non-reflective flat safety glass cover, hinged, provide superior illumination and glare control. The luminaire is factory-sealed and does not need to be opened during installation. RFL110 post top variant with spigot size Ø 76 x 85 mm. Ø 60 x 100 mm with corresponding reducer available as an option. Must be indicated during order placement.

Contact WE-EF direct or your local WE-EF sales representative for an individual solution designed to precisely meet your needs.

IMPORTANT

Photometric data legend (for ies-data):
Part ID (channel I+II - both colour temperatures 1850K (True Amber) + 2200K / 2200K + 3000K)

Part ID_1 (channel I - lower colour temperature 1850K
(True Amber) / 2200K only)

Part ID_2 (channel II - upper colour temperature 2200K /
3000K only)

Photometric data legend (for ldt-data):

Part ID (channel I+II - both colour temperatures 1850K
(True Amber) + 2200K / 2200K + 3000K)

Part ID (channel I - lower colour temperature 1850K (True
Amber) / 2200K only)

Part ID (channel II - upper colour temperature 2200K /
3000K only)

Photometric files (IES, LDT) for light distributions [S65]
[S70] [P65] [R60] [A60] with Backlight Shield on request.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Non-reflective safety glass lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium	RAL7016 Anthracite grey
	RAL9016 Traffic white			
Gasket	CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK08			
Corrosion resistance	5CE			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Power factor	> 0.9
Surge protection	6/6kV, optional 10kV

Additional information

Windage	0.140 m ²
Lifetime	C-D (Light source)

Options

Light distribution



[A60] asymmetric, forward throw



[S65] asymmetric, side throw



[S70] asymmetric, side throw



[R60] rectangular, side throw



[S60] asymmetric, side throw



[P65] pedestrian/bicycle lane

Colour temperature



2200K









1850K

Nominal Watt

8 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[A60] asymmetric, forward throw</p>	111-2084	LED-8/8W/1850K-8/16W/2200K	2248.3 lm	8 W	Amber&70
	111-2085	LED-8/8W/1850K-8/16W/3000K	2818.8 lm	8 W	60&80
	111-2083	LED-8/8W/2200K-8/16W/3000K	2919.4 lm	8 W	70&80
 <p>[P65] pedestrian/bicycle lane</p>	111-2102	LED-8/8W/1850K-8/16W/2200K	2382.8 lm	8 W	Amber&70
	111-2103	LED-8/8W/1850K-8/16W/3000K	2987.4 lm	8 W	60&80
	111-2101	LED-8/8W/2200K-8/16W/3000K	3094.1 lm	8 W	70&80
 <p>[R60] rectangular, side throw</p>	111-2093	LED-8/8W/1850K-8/16W/2200K	2307.7 lm	8 W	Amber&70
	111-2094	LED-8/8W/1850K-8/16W/3000K	2893.2 lm	8 W	60&80
	111-2092	LED-8/8W/2200K-8/16W/3000K	2996.6 lm	8 W	70&80
 <p>[S60] asymmetric, side throw</p>	111-2099	LED-8/8W/1850K-8/16W/2200K	2560.1 lm	8 W	Amber&70
	111-2098	LED-8/8W/2200K-8/16W/3000K	3324.4 lm	8 W	70&80
 <p>[S65] asymmetric, side throw</p>	111-2087	LED-8/8W/1850K-8/16W/2200K	2469 lm	8 W	Amber&70
	111-2088	LED-8/8W/1850K-8/16W/3000K	3095.4 lm	8 W	60&80
	111-2086	LED-8/8W/2200K-8/16W/3000K	3206 lm	8 W	70&80
 <p>[S70] asymmetric, side throw</p>	111-2090	LED-8/8W/1850K-8/16W/2200K	2434.5 lm	8 W	Amber&70
	111-2091	LED-8/8W/1850K-8/16W/3000K	3052.2 lm	8 W	60&80
	111-2089	LED-8/8W/2200K-8/16W/3000K	3161.2 lm	8 W	70&80