



Pole-Mounted Luminaires

RFL120-SE-WL

The RFL110 features an elegant round shape, designed with the future in mind, offering a full suite of connectivity options. Post top installation on poles, seamlessly blending into urban landscapes by day and night.

Constructed from marine-grade, die-cast aluminium alloy, with an IP66 rating, 5CE superior corrosion protection including PCS hardware and CCG® Controlled Compression Gasket. Non-reflective flat safety glass cover, hinged.

Integral EC electronic converter, class I. OLC® One LED Concept CAD-optimised optics and non-reflective flat safety glass cover, hinged, provide superior illumination and glare control. The luminaire is factory-sealed and does not need to be opened during installation. RFL110-SE with spigot size Ø 42 x 100 mm.

Contact WE-EF direct or your local WE-EF sales representative for an individual solution designed to precisely meet your needs.

IMPORTANT

Photometric data legend (for ies-data):

Part ID (channel I+II - both colour temperatures 1850K (True Amber) + 2200K / 2200K + 3000K)

Part ID_1 (channel I - lower colour temperature 1850K (True Amber) / 2200K only)

Part ID_2 (channel II - upper colour temperature 2200K / 3000K only)

Photometric data legend (for ldt-data):

Part ID (channel I+II - both colour temperatures 1850K (True Amber) + 2200K / 2200K + 3000K)

Side-entry

Variant

IP66 / IK08


IP / IK

Part ID (channel I - lower colour temperature 1850K (True Amber) / 2200K only)
Part ID (channel II - upper colour temperature 2200K / 3000K only)

Lighting

Light distribution Colour temperature Wattage

Physical description



Length	590 mm
Diameter	510 mm
Weight	9.3 kg
Body	Marine-grade, die-cast aluminium alloy
Lens	Non-reflective safety glass lens
Colours	RAL7016 RAL9004 RAL9007 RAL9016 Anthracite grey Signal black Grey aluminium Traffic white
Gasket	CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Mounting	Side-entry
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE
Windage	0.211 m²

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Cable	1.5 m connection cable with QPD connector
Surge protection	SP10

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
--------------------	---------	--------------	--------------	-------------------	-----

Pole-Mounted Luminaires

RFL120-SE-WL

we-ef

A Fagerhult Group Company

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn
Phone: +66 2 738 96 20
Fax: +66 2 738 96 29
<https://we-ef.com/asia>

Subject to technical changes and errors.
