


Description

Wall and pole mounted luminaire.



IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Non-reflecting safety glass lens hinged, tool-less entry. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Recommended mounting height 10-20 ft, depending on wattage and light distribution selected.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Non-reflecting safety glass lens, hinged			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			










Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	C-D (Light source)




Additional information

Height x Diameter (inches)	3.94 x 18.11
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.3 ft ²
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [S60] Type III Short	 3000K	24 W
		48 W
 [S70] Type II Short	 4000K	12 W
		72 W
 [A60] Type IV Very Short	 2700K	
 [S65] Type III Medium		
 [R65]		
 [P65] Type II Medium		

Configurations



Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	111-1046	LED-12/12W/2700K	1522 lm	12 W	80
	111-0455	LED-12/12W/3000K	1626.9 lm	12 W	80
	111-0414	LED-12/12W/4000K	1784.4 lm	12 W	80
	111-1047	LED-12/24W/2700K	2692.3 lm	24 W	80
	111-0275	LED-12/24W/3000K	2891.7 lm	24 W	80
	111-0353	LED-12/24W/4000K	3091.2 lm	24 W	80
	111-1048	LED-24/24W/2700K	3043.9 lm	24 W	80
	111-0457	LED-24/24W/3000K	3253.8 lm	24 W	80
	111-0415	LED-24/24W/4000K	3568.7 lm	24 W	80
	111-1049	LED-24/48W/2700K	5384.6 lm	48 W	80
	111-0277	LED-24/48W/3000K	5783.5 lm	48 W	80
	111-0355	LED-24/48W/4000K	6182.3 lm	48 W	80
	111-1050	LED-24/72W/2700K	8753.5 lm	72 W	80
	111-1050-70	LED-24/72W/2700K	10034.5 lm	72 W	70
	111-0908	LED-24/72W/3000K	9180.5 lm	72 W	80
	111-0909	LED-24/72W/4000K	9607.5 lm	72 W	80
 <p>[P65] Type II Medium</p>	111-1051	LED-12/12W/2700K	1578.1 lm	12 W	80
	111-0780	LED-12/12W/3000K	1687 lm	12 W	80
	111-1052	LED-12/24W/2700K	2850.5 lm	24 W	80
	111-0827	LED-12/24W/3000K	3061.6 lm	24 W	80
	111-1053	LED-24/24W/2700K	3156.3 lm	24 W	80
	111-0791	LED-24/24W/3000K	3374 lm	24 W	80
	111-1054	LED-24/48W/2700K	5700.9 lm	48 W	80
	111-0828	LED-24/48W/3000K	6123.2 lm	48 W	80
	111-1055	LED-24/72W/2700K	8682 lm	72 W	80
	111-0910	LED-24/72W/3000K	9105.5 lm	72 W	80
	111-0911	LED-24/72W/4000K	9529 lm	72 W	80
 <p>[R65]</p>	111-1041	LED-12/12W/2700K	1518.8 lm	12 W	80
	111-0467	LED-12/12W/3000K	1623.5 lm	12 W	80
	111-0416	LED-12/12W/4000K	1780.6 lm	12 W	80
	111-1042	LED-12/24W/2700K	2686.3 lm	24 W	80
	111-0469	LED-12/24W/3000K	2885.3 lm	24 W	80

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/11/2026


Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	111-0417	LED-12/24W/4000K	3084.3 lm	24 W	80
	111-1043	LED-24/24W/2700K	3037.5 lm	24 W	80
	111-0471	LED-24/24W/3000K	3247 lm	24 W	80
	111-0418	LED-24/24W/4000K	3561.2 lm	24 W	80
	111-1044	LED-24/48W/2700K	5372.6 lm	48 W	80
	111-0473	LED-24/48W/3000K	5770.6 lm	48 W	80
	111-0419	LED-24/48W/4000K	6168.6 lm	48 W	80
	111-1045	LED-24/72W/2700K	8636.1 lm	72 W	80
	111-0912	LED-24/72W/3000K	9057.4 lm	72 W	80
	111-0913	LED-24/72W/4000K	9478.6 lm	72 W	80
	[S60] Type III Short	111-1026	LED-12/12W/2700K	1612.9 lm	12 W
	111-0447	LED-12/12W/3000K	1724.1 lm	12 W	80
	111-0406	LED-12/12W/4000K	1891 lm	12 W	80
	111-1027	LED-12/24W/2700K	2911.3 lm	24 W	80
	111-0192	LED-12/24W/3000K	3126.9 lm	24 W	80
	111-0337	LED-12/24W/4000K	3342.6 lm	24 W	80
	111-1028	LED-24/24W/2700K	3225.8 lm	24 W	80
	111-0449	LED-24/24W/3000K	3448.3 lm	24 W	80
	111-0407	LED-24/24W/4000K	3782 lm	24 W	80
	111-1029	LED-24/48W/2700K	5822.5 lm	48 W	80
	111-0193	LED-24/48W/3000K	6253.8 lm	48 W	80
	111-0339	LED-24/48W/4000K	6685.1 lm	48 W	80
	111-1030	LED-24/72W/2700K	9122.7 lm	72 W	80
	111-0914	LED-24/72W/3000K	9567.7 lm	72 W	80
	111-0915	LED-24/72W/4000K	10012.7 lm	72 W	80
	111-1031	LED-12/12W/2700K	1614.7 lm	12 W	80
	111-0459	LED-12/12W/3000K	1726 lm	12 W	80
	111-0408	LED-12/12W/4000K	1893.1 lm	12 W	80
	111-1032	LED-12/24W/2700K	2916 lm	24 W	80
	111-0461	LED-12/24W/3000K	3132 lm	24 W	80
	111-0409	LED-12/24W/4000K	3348 lm	24 W	80
	111-1033	LED-24/24W/2700K	3229.4 lm	24 W	80
	111-0463	LED-24/24W/3000K	3452.1 lm	24 W	80

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/11/2026

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [S70] Type II Short	111-0410	LED-24/24W/4000K	3786.2 lm	24 W	80
	111-1034	LED-24/48W/2700K	5832.1 lm	48 W	80
	111-0465	LED-24/48W/3000K	6264.1 lm	48 W	80
	111-0411	LED-24/48W/4000K	6696.1 lm	48 W	80
	111-1035	LED-24/72W/2700K	9164.3 lm	72 W	80
	111-0916	LED-24/72W/3000K	9611.3 lm	72 W	80
	111-0917	LED-24/72W/4000K	10058.4 lm	72 W	80
	111-1036	LED-12/12W/2700K	1566.6 lm	12 W	80
	111-0451	LED-12/12W/3000K	1674.6 lm	12 W	80
	111-0412	LED-12/12W/4000K	1836.7 lm	12 W	80
	111-1037	LED-12/24W/2700K	2778.3 lm	24 W	80
	111-0230	LED-12/24W/3000K	2984.1 lm	24 W	80
	111-0345	LED-12/24W/4000K	3189.9 lm	24 W	80
	111-1038	LED-24/24W/2700K	3133.2 lm	24 W	80
	111-0453	LED-24/24W/3000K	3349.3 lm	24 W	80
	111-0413	LED-24/24W/4000K	3673.4 lm	24 W	80
	111-0862	LED-24/48W/2700K	5556.5 lm	48 W	80
	111-0234	LED-24/48W/3000K	5968.1 lm	48 W	80
	111-0347	LED-24/48W/4000K	6379.7 lm	48 W	80
	111-1040	LED-24/72W/2700K	8781.9 lm	72 W	80
111-0918	LED-24/72W/3000K	9210.3 lm	72 W	80	
111-0919	LED-24/72W/4000K	9638.6 lm	72 W	80	