

Description

Wall and pole mounted LED luminaire.

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Non-reflecting safety glass lens hinged, tool-less entry. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Recommended mounting height 10-30 ft, depending on wattage and light distribution selected.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

For DarkSky compliant configurations of this product,

please find the spec sheet and DarkSky certificate in the library.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Non-reflecting safety glass lens, hinged			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			











Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	C-D (Light source)




Additional information

Height x Diameter (inches)	4.73 x 22.44
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.5 ft ²
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [S60] Type III Short	 3000K	96 W
		72 W
 [S70] Type II Short	 4000K	36 W
		48 W
 [A60] Type IV Very Short	 2700K	108 W
		144 W
 [S65] Type III Medium		
 [R65]		
 [P45L]		
 [P45R]		

Configurations



Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	111-1080	LED-36/36W/2700K	4565.9 lm	36 W	80
	111-0491	LED-36/36W/3000K	4880.8 lm	36 W	80
	111-0428	LED-36/36W/4000K	5353.1 lm	36 W	80
	111-1081	LED-36/72W/2700K	8076.9 lm	72 W	80
	111-0283	LED-36/72W/3000K	8675.2 lm	72 W	80
	111-0357	LED-36/72W/4000K	9273.5 lm	72 W	80
	111-1082	LED-36/108W/2700K	13130.2 lm	108 W	80
	111-0920	LED-36/108W/3000K	13770.7 lm	108 W	80
	111-0921	LED-36/108W/4000K	14411.2 lm	108 W	80
	111-1083	LED-48/48W/2700K	6087.8 lm	48 W	80
	111-0493	LED-48/48W/3000K	6507.7 lm	48 W	80
	111-0429	LED-48/48W/4000K	7137.5 lm	48 W	80
	111-1084	LED-48/96W/2700K	10769.2 lm	96 W	80
	111-0285	LED-48/96W/3000K	11566.9 lm	96 W	80
	111-0359	LED-48/96W/4000K	12364.6 lm	96 W	80
	111-1085	LED-48/144W/2700K	17507 lm	144 W	80
	111-0930	LED-48/144W/3000K	18361 lm	144 W	80
111-0931	LED-48/144W/4000K	19215 lm	144 W	80	
 <p>[P45L]</p>	111-0888	LED-36/72W/3000K	9768.2 lm	72 W	80
	111-0889	LED-36/72W/4000K	10441.9 lm	72 W	80
	111-0892	LED-48/96W/3000K	13024.3 lm	96 W	80
	111-0893	LED-48/96W/4000K	13922.5 lm	96 W	80
 <p>[P45R]</p>	111-1086	LED-36/72W/2700K	9094.5 lm	72 W	80
	111-0890	LED-36/72W/3000K	9768.2 lm	72 W	80
	111-0891	LED-36/72W/4000K	10441.9 lm	72 W	80
	111-1087	LED-48/96W/2700K	12126 lm	96 W	80
	111-0894	LED-48/96W/3000K	13024.3 lm	96 W	80
	111-0895	LED-48/96W/4000K	13922.5 lm	96 W	80
	111-1074	LED-36/36W/2700K	4556.3 lm	36 W	80
111-0495	LED-36/36W/3000K	4870.5 lm	36 W	80	
111-0430	LED-36/36W/4000K	5341.8 lm	36 W	80	

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/11/2026



Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
 [R65]	111-1075	LED-36/72W/2700K	8058.9 lm	72 W	80	
	111-0497	LED-36/72W/3000K	8655.9 lm	72 W	80	
	111-0431	LED-36/72W/4000K	9252.8 lm	72 W	80	
	111-1076	LED-36/108W/2700K	12954.2 lm	108 W	80	
	111-0922	LED-36/108W/3000K	13586.1 lm	108 W	80	
	111-0923	LED-36/108W/4000K	14218 lm	108 W	80	
	111-1077	LED-48/48W/2700K	6075 lm	48 W	80	
	111-0944	LED-48/48W/3000K	6494 lm	48 W	80	
	111-0432	LED-48/48W/4000K	7122.4 lm	48 W	80	
	111-1078	LED-48/96W/2700K	10745.2 lm	96 W	80	
	111-0501	LED-48/96W/3000K	11541.2 lm	96 W	80	
	111-0433	LED-48/96W/4000K	12337.1 lm	96 W	80	
	111-1079	LED-48/144W/2700K	17272.2 lm	144 W	80	
	111-0932	LED-48/144W/3000K	18114.8 lm	144 W	80	
	111-0933	LED-48/144W/4000K	18957.3 lm	144 W	80	
	 [S60] Type III Short	111-1056	LED-36/36W/2700K	4838.7 lm	36 W	80
		111-0475	LED-36/36W/3000K	5172.4 lm	36 W	80
111-0420		LED-36/36W/4000K	5673 lm	36 W	80	
111-1057		LED-36/72W/2700K	8733.8 lm	72 W	80	
111-0190		LED-36/72W/3000K	9380.8 lm	72 W	80	
111-0341		LED-36/72W/4000K	10027.7 lm	72 W	80	
111-1058		LED-36/108W/2700K	13684 lm	108 W	80	
111-0924		LED-36/108W/3000K	14351.5 lm	108 W	80	
111-0925		LED-36/108W/4000K	15019.1 lm	108 W	80	
111-1059		LED-48/48W/2700K	6451.6 lm	48 W	80	
111-0477		LED-48/48W/3000K	6896.5 lm	48 W	80	
111-0421		LED-48/48W/4000K	7563.9 lm	48 W	80	
111-1060		LED-48/96W/2700K	11645.1 lm	96 W	80	
111-0188		LED-48/96W/3000K	12507.7 lm	96 W	80	
111-0343		LED-48/96W/4000K	13370.3 lm	96 W	80	
111-1061		LED-48/144W/2700K	18245.4 lm	144 W	80	
111-0934		LED-48/144W/3000K	19135.4 lm	144 W	80	
111-0935		LED-48/144W/4000K	20025.4 lm	144 W	80	

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/11/2026

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [S65] Type III Medium	111-1062	LED-36/36W/2700K	4844.1 lm	36 W	80
	111-0479	LED-36/36W/3000K	5178.1 lm	36 W	80
	111-0479-70	LED-36/36W/3000K	6013.3 lm	36 W	70
	111-0422	LED-36/36W/4000K	5679.2 lm	36 W	80
	111-0422-70	LED-36/36W/4000K	6347.4 lm	36 W	70
	111-1063	LED-36/72W/2700K	8748.1 lm	72 W	80
	111-0481	LED-36/72W/3000K	9396.1 lm	72 W	80
	111-0423	LED-36/72W/4000K	10044.1 lm	72 W	80
	111-1064	LED-36/108W/2700K	13746.4 lm	108 W	80
	111-0926	LED-36/108W/3000K	14417 lm	108 W	80
	111-0927	LED-36/108W/4000K	15087.5 lm	108 W	80
	111-1065	LED-48/48W/2700K	6458.8 lm	48 W	80
	111-0483	LED-48/48W/3000K	6904.2 lm	48 W	80
	111-0424	LED-48/48W/4000K	7572.3 lm	48 W	80
	111-1066	LED-48/96W/2700K	11664.1 lm	96 W	80
	111-0485	LED-48/96W/3000K	12528.2 lm	96 W	80
	111-0425	LED-48/96W/4000K	13392.2 lm	96 W	80
	111-1067	LED-48/144W/2700K	18328.6 lm	144 W	80
	111-0936	LED-48/144W/3000K	19222.6 lm	144 W	80
111-0937	LED-48/144W/4000K	20116.7 lm	144 W	80	
 [S70] Type II Short	111-1068	LED-36/36W/2700K	4699.8 lm	36 W	80
	111-0487	LED-36/36W/3000K	5023.9 lm	36 W	80
	111-0426	LED-36/36W/4000K	5510.1 lm	36 W	80
	111-1069	LED-36/72W/2700K	8334.8 lm	72 W	80
	111-0228	LED-36/72W/3000K	8952.2 lm	72 W	80
	111-0349	LED-36/72W/4000K	9569.6 lm	72 W	80
	111-1070	LED-36/108W/2700K	13172.8 lm	108 W	80
	111-0928	LED-36/108W/3000K	13815.4 lm	108 W	80
	111-0929	LED-36/108W/4000K	14458 lm	108 W	80
	111-1071	LED-48/48W/2700K	6266.4 lm	48 W	80
	111-0489	LED-48/48W/3000K	6698.6 lm	48 W	80
	111-0427	LED-48/48W/4000K	7346.8 lm	48 W	80
	111-1072	LED-48/96W/2700K	11113.1 lm	96 W	80

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/11/2026

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	111-0218	LED-48/96W/3000K	11936.2 lm	96 W	80
	111-0351	LED-48/96W/4000K	12759.4 lm	96 W	80
	111-1073	LED-48/144W/2700K	17563.7 lm	144 W	80
	111-0938	LED-48/144W/3000K	18420.5 lm	144 W	80
	111-0939	LED-48/144W/4000K	19277.3 lm	144 W	80
