

**Description**

Surface-mounted wall or ceiling luminaire.

ADA (American Disabilities Act) Compliant.

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Luminaire can be mounted for up or down lighting. Suitable for installation on ceiling or wall over 4" recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK08			




### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Surge protection	1/2 kV




### Additional information

Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

Light distribution	Color temperature	Nominal Watt
 <p>[R45] rectangular asymmetric Type II</p>	12W [R45]	6 W 12 W
 <p>[M] symmetric, medium beam</p>	2,7K [R45]	
 <p>[N] bi-symmetric, narrow beam</p>	18W [R45]	
	26W [R45]	
	12W [M]	
	2,7K [M]	
	18W [M]	
	26W [M]	
	12W [N]	
	2,7K [N]	
	18W [N]	
	26W [N]	

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M] symmetric, medium beam</p>	131-9986_us	LED-2/6W/12W [M]	1397.1 lm	6 W	80
	131-9987_us	LED-2/6W/12W [M]	1493.4 lm	6 W	80
	131-9988_us	LED-2/6W/18W [M]	2039.7 lm	6 W	80
	131-9989_us	LED-2/6W/18W [M]	2134.6 lm	6 W	80
	131-9614_us	LED-2/6W/18W [M]	1944.8 lm	6 W	80
	131-9990_us	LED-2/6W/26W [M]	2608.9 lm	6 W	80
	131-9991_us	LED-2/6W/26W [M]	2727.5 lm	6 W	80
	131-9615_us	LED-2/6W/26W [M]	2466.6 lm	6 W	80
	131-9613_us	LED-6/12W/2,7K [M]	1300.7 lm	12 W	80
 <p>[N] bi-symmetric, narrow beam</p>	131-9992_us	LED-2/6W/12W [N]	1313.8 lm	6 W	80
	131-9993_us	LED-2/6W/12W [N]	1404.4 lm	6 W	80
	131-9994_us	LED-2/6W/18W [N]	2068.5 lm	6 W	80
	131-9995_us	LED-2/6W/18W [N]	2164.7 lm	6 W	80
	131-9617_us	LED-2/6W/18W [N]	1972.3 lm	6 W	80
	131-9996_us	LED-2/6W/26W [N]	2645.8 lm	6 W	80
	131-9997_us	LED-2/6W/26W [N]	2766.1 lm	6 W	80
	131-9618_us	LED-2/6W/26W [N]	2501.5 lm	6 W	80
	131-9616_us	LED-6/12W/2,7K [N]	1223.2 lm	12 W	80
 <p>[R45] rectangular asymmetric Type II</p>	131-9980_us	LED-2/6W/12W [R45]	1096.4 lm	6 W	80
	131-9981_us	LED-2/6W/12W [R45]	1172 lm	6 W	80
	131-9982_us	LED-2/6W/18W [R45]	1540.2 lm	6 W	80
	131-9983_us	LED-2/6W/18W [R45]	1611.9 lm	6 W	80
	131-9611_us	LED-2/6W/18W [R45]	1468.6 lm	6 W	80
	131-9984_us	LED-2/6W/26W [R45]	1970.1 lm	6 W	80
	131-9985_us	LED-2/6W/26W [R45]	2059.6 lm	6 W	80
	131-9612_us	LED-2/6W/26W [R45]	1862.6 lm	6 W	80
	131-9610_us	LED-6/12W/2,7K [R45]	1020.8 lm	12 W	80