

Description

IP66, Class I. IK06. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone CCG_R_ Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept.

Specifications

Material description

Colours

RAL9004

Signal black

RAL9006

White aluminium

RAL9007

Grey aluminium

Corrosion resistance 5CE+Primer

Electrical description

Additional information

Options

Light distribution



[B] symmetric, wide beam



[EES] symmetric, very narrow beam, sharp cut-off



[M] symmetric, medium beam




[EE] symmetric, very narrow beam

Colour temperature



3000K







4000K

Nominal Watt

12 W

18 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	138-8996	LED-6/12W/3000K	1347.1 lm	12 W	80
	138-8998	LED-6/12W/4000K	1440 lm	12 W	80
	138-6000	LED-6/18W/3000K	2018.8 lm	18 W	80
	138-6003	LED-6/18W/4000K	2112.7 lm	18 W	80
 [EE] symmetric, very narrow beam	138-9003	LED-6/12W/3000K	1496.5 lm	12 W	80
	138-9006	LED-6/12W/4000K	1599.7 lm	12 W	80
	138-6002	LED-6/18W/3000K	2165.6 lm	18 W	80
	138-6005	LED-6/18W/4000K	2266.4 lm	18 W	80
 [EES] symmetric, very narrow beam, sharp cut-off	138-8997	LED-6/12W/3000K	1610.7 lm	12 W	80
	138-8999	LED-6/12W/4000K	1721.8 lm	12 W	80
 [M] symmetric, medium beam	138-9002	LED-6/12W/3000K	1511.8 lm	12 W	80
	138-9005	LED-6/12W/4000K	1616.1 lm	12 W	80
	138-6001	LED-6/18W/3000K	2167.2 lm	18 W	80
	138-6004	LED-6/18W/4000K	2268 lm	18 W	80