

## Description

IP66, Class I. IK06. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone CCG\_R\_ Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept.

## Specifications

### Material description

---

Colours

**RAL9004**

Signal black

**RAL9006**

White aluminium

**RAL9007**

Grey aluminium

Corrosion resistance

5CE+Primer

---

### Electrical description

### Additional information

**Options****Light distribution    Colour temperature    Nominal Watt**

[B]




3000K

12 W

18 W



[EES]



4000K







[M]



[EE]

## Configurations

| Light distribution   | Part ID  | Light source    | Rated lumens | Rated input power | CRI |
|--|----------|-----------------|--------------|-------------------|-----|
| <br>[B]    | 138-8996 | LED-6/12W/3000K | 1347.1 lm    | 12 W              | 80  |
|  | 138-8998 | LED-6/12W/4000K | 1440 lm      | 12 W              | 80  |
|  | 138-6000 | LED-6/18W/3000K | 2018.8 lm    | 18 W              | 80  |
|  | 138-6003 | LED-6/18W/4000K | 2112.7 lm    | 18 W              | 80  |
| <br>[EE]  | 138-9003 | LED-6/12W/3000K | 1496.5 lm    | 12 W              | 80  |
|  | 138-9006 | LED-6/12W/4000K | 1599.7 lm    | 12 W              | 80  |
|  | 138-6002 | LED-6/18W/3000K | 2165.6 lm    | 18 W              | 80  |
|  | 138-6005 | LED-6/18W/4000K | 2266.4 lm    | 18 W              | 80  |
| <br>[EES] | 138-8997 | LED-6/12W/3000K | 1610.7 lm    | 12 W              | 80  |
|  | 138-8999 | LED-6/12W/4000K | 1721.8 lm    | 12 W              | 80  |
| <br>[M] | 138-9002 | LED-6/12W/3000K | 1511.8 lm    | 12 W              | 80  |
|  | 138-9005 | LED-6/12W/4000K | 1616.1 lm    | 12 W              | 80  |
|  | 138-6001 | LED-6/18W/3000K | 2167.2 lm    | 18 W              | 80  |
|  | 138-6004 | LED-6/18W/4000K | 2268 lm      | 18 W              | 80  |