

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. PMMA lens. Silicone CCG_R_ Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept.

Specifications

Material description

Colours

RAL9004

Signal black

RAL9006

White aluminium

RAL9007

Grey aluminium

Corrosion resistance 5CE+Primer

Electrical description

Additional information

Options

Light distribution



[B] symmetric, wide beam



[EES] symmetric, very narrow beam, sharp cut-off



[M] symmetric, medium beam




[EE] symmetric, very narrow beam

Colour temperature



3000K







4000K

Nominal Watt

24 W

36 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B] symmetric, wide beam	138-8992	LED-12/24W/3000K	2709.2 lm	24 W	80
	138-8994	LED-12/24W/4000K	2896 lm	24 W	80
	138-6006	LED-12/36W/3000K	3795.1 lm	36 W	80
	138-6009	LED-12/36W/4000K	3971.6 lm	36 W	80
 [EE] symmetric, very narrow beam	138-9011	LED-12/24W/3000K	2883.7 lm	24 W	80
	138-9014	LED-12/24W/4000K	3082.5 lm	24 W	80
	138-6008	LED-12/36W/3000K	4093.2 lm	36 W	80
	138-6011	LED-12/36W/4000K	4283.6 lm	36 W	80
 [EES] symmetric, very narrow beam, sharp cut-off	138-8993	LED-12/24W/3000K	3077.9 lm	24 W	80
	138-8995	LED-12/24W/4000K	3290.2 lm	24 W	80
 [M] symmetric, medium beam	138-9010	LED-12/24W/3000K	2998.6 lm	24 W	80
	138-9013	LED-12/24W/4000K	3205.4 lm	24 W	80
	138-6007	LED-12/36W/3000K	4325.2 lm	36 W	80
	138-6010	LED-12/36W/4000K	4526.4 lm	36 W	80