


Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter.




A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Polycarbonate lens
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP55
Impact resistance	IK10
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)




Additional information

Lifetime	Ta=25° L80B10 > 54000h
----------	------------------------

Options

Light distribution **Colour temperature** **Nominal Watt**

[]

	3000K
	4000K
	2700K

4 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	133-0450	LED-4/4W/2700K	70.3 lm	4 W	80
	133-0333	LED-4/4W/3000K	75.1 lm	4 W	80
	133-0334	LED-4/4W/4000K	82.4 lm	4 W	80