




Description

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.



Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9006 White aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
□	3K RD	6 W
	4K RD	
	2.7K RD	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	190-9051	LED-2/6W/2.7K RD	161.1 lm	6 W	80
	190-9043	LED-2/6W/3K RD	170.9 lm	6 W	80
	190-9047	LED-2/6W/4K RD	180.7 lm	6 W	80