


### Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter. Optional 2200 K version available. To be specified at time of ordering.



A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Polycarbonate lens			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C (Light source)

### Additional information

Lifetime	Ta=25° L80B10 > 54000h
----------	------------------------

**Options**

**Light distribution**    **Colour temperature**    **Nominal Watt**

[]



3000K

4 W



4000K



2700K

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	133-0453	LED-4/4W/2700K	16 lm	4 W	80
	133-0324	LED-4/4W/3000K	17.1 lm	4 W	80
	133-0335	LED-4/4W/4000K	18.7 lm	4 W	80