



Description

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry. Second cable entry for through wiring available on request.

Specifications

Material description

| | | | | |
|--------------------|--------------------------------|----------------------------------|-----------------------------------|---------------------------------|
| Colours | RAL9004 Signal black | RAL9007 Grey aluminium | RAL7016 Anthracite grey | RAL9016 Traffic white |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|------------------|----------------------------------|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral EC electronic converter |

Additional information

Options

| Light distribution | Colour temperature | Nominal Watt |
|--------------------|--------------------|--------------|
| □ | 3K SD | 5 W |
| | 4K SD | |
| | 2.7K SD | |

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--------------------|----------|------------------|--------------|-------------------|-----|
| [] | 190-9060 | LED-2/5W/2.7K SD | 75.4 lm | 5 W | 80 |
| | 190-9001 | LED-2/5W/3K SD | 78.6 lm | 5 W | 80 |
| | 190-9055 | LED-2/5W/4K SD | 81.7 lm | 5 W | 80 |