



Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry.

Specifications

Material description

Colours



Stainless Steel

Fasteners

PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection

IP66

Impact resistance

IK07

Corrosion resistance

5CE+Primer

Electrical description

Power supply

230V / 50 Hz

Energy efficiency

The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
□	3K RD	5 W
	4K RD	
	2.7K RD	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	190-9052	LED-2/5W/2.7K RD	75.4 lm	5 W	80
	190-9044	LED-2/5W/3K RD	78.6 lm	5 W	80
	190-9048	LED-2/5W/4K RD	81.7 lm	5 W	80