STO134 LED Shallow Depth - Stainless Steel



Description

IP66. IK07. Marine-grade, die-cast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry. Second cable entry for through wiring available on request.

Specifications

Material description

Colours	Stainless Steel
Ingress protection	IP66
Impact resistance	IK07

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
[]		5 W
	3K SD	
	4K SD	
	2.7K SD	

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	190-9063	LED-2/5W/2.7K SD	75.4 lm	5 W	80
	190-9013	LED-2/5W/3K SD	78.6 lm	5 W	80
	190-9058	LED-2/5W/4K SD	81.7 lm	5 W	80

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia