





### Description

Low glare steplight.

ADA (American Disabilities Act) Compliant.


IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



## Specifications

### Material description

Body	Luminaire body and lens frame constructed in die cast aluminum.			
Lens	Prismatic polycarbonate lens.			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS polymer coated stainless steel			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information

Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L80B10 > 54000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**

[]

0 W

6 W



2700K

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
[]	133-0350_us		211.5 lm	0 W	80
	133-0351_us		232 lm	0 W	80
	133-0456	LED-6/6W/2700K	197.8 lm	6 W	80