





Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. Two cable entries. Factory installed LED circuit board. Integral EC electronic converter. Optional 2200 K version available. To be specified at time of ordering.

A pre-installation blockout is available and recommended for mounting in concrete walls. To be ordered separately.

Specifications

Material description

| | | | | | | | | | |
|----------------------------------|---|---------------------------------|-----------------------------------|---------------------------------|-----------------------------------|----------------------------------|--|--|--|
| Body | Marine-grade, die-cast aluminium alloy | | | | | | | | |
| Lens | Polycarbonate lens | | | | | | | | |
| Colours | <table><tr><td>RAL9004 Signal black</td><td>RAL9006 White aluminium</td><td>RAL9016 Traffic white</td><td>RAL7016 Anthracite grey</td></tr><tr><td>RAL9007 Grey aluminium</td><td></td><td></td><td></td></tr></table> | RAL9004 Signal black | RAL9006 White aluminium | RAL9016 Traffic white | RAL7016 Anthracite grey | RAL9007 Grey aluminium | | | |
| RAL9004 Signal black | RAL9006 White aluminium | RAL9016 Traffic white | RAL7016 Anthracite grey | | | | | | |
| RAL9007 Grey aluminium | | | | | | | | | |
| Gasket | Silicone rubber gasket | | | | | | | | |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware | | | | | | | | |
| Ingress protection | IP55 | | | | | | | | |
| Impact resistance | IK10 | | | | | | | | |
| Corrosion resistance | 5CE | | | | | | | | |

Electrical description

| | |
|-------------------|---------------------------|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral ECG control gear |
| Surge protection | 1/2 kV |
| Energy efficiency | C-D (Light source) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L80B10 > 54000h |
|----------|------------------------|

Options

Light distribution **Colour temperature** **Nominal Watt**

[]



3000K

6 W



4000K



2700K

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--------------------|----------|----------------|--------------|-------------------|-----|
| [] | 133-0456 | LED-6/6W/2700K | 197.8 lm | 6 W | 80 |
| | 133-0350 | LED-6/6W/3000K | 211.5 lm | 6 W | 80 |
| | 133-0351 | LED-6/6W/4000K | 232 lm | 6 W | 80 |