

### Description

Vertically oriented louvered steplight.

ADA (American Disabilities Act) Compliant.

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-installation blockout is recommended for mounting in concrete, available on request.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Polycarbonate			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	C (Light source)



### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L80B10 > 54000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**

[]

	4000K
	3000K
	2700K

6 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
[]	190-9040	LED-2/6W/2700K	17.6 lm	6 W	80
	190-9017_us	LED-2/6W/3000K	18.7 lm	6 W	80
	190-9018_us	LED-2/6W/4000K	19.8 lm	6 W	80