

Description

Vertically oriented louvered steplight.

ADA (American Disabilities Act) Compliant.

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-installation blackout is recommended for mounting in concrete, available on request.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Polycarbonate			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	C (Light source)



Additional information

Length x Width (inches)	10.63 x 2.55
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L80B10 > 54000h

Options

Light distribution **Color temperature** **Nominal Watt**

[]

	4000K
	3000K
	2700K

6 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
□	190-9040	LED-2/6W/2700K	17.6 lm	6 W	80
	190-9017	LED-2/6W/3000K	18.7 lm	6 W	80
	190-9018	LED-2/6W/4000K	19.8 lm	6 W	80