

Description

Vertically oriented, louvered steplight.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

| | | | | |
|----------------------|--|---------------------------------|------------------------------|----------------------------------|
| Body | Luminaire body and lens frame constructed in die cast aluminum | | | |
| Lens | Opal polycarbonate lens. | | | |
| Colors | RAL9004 Signal black | RAL9016 Traffic white | RAL8019 Grey brown | RAL9007 Grey aluminium |
| Gasket | Silicone rubber gasket | | | |
| Fasteners | PCS polymer coated stainless steel | | | |
| Ingress protection | IP55 | | | |
| Impact resistance | IK10 | | | |
| Corrosion resistance | 5CE | | | |


Electrical description

| | |
|-------------------|---|
| Power supply | 120-277V / 50-60 Hz 0-10 V dimmable driver. |
| Driver / Ballast | Integral EC electronic converter |
| Surge protection | 1/2 kV |
| Energy efficiency | C-D (Light source) |

Additional information

| | |
|----------|---|
| Listings | ETL listed. Suitable for wet locations. |
| Lifetime | Ta=25°/40° L80B10 > 54000h |

Options

| Light distribution | Color temperature | Nominal Watt |
|--------------------|---|--------------|
| □ | | 0 W |
| |  2700K | 6 W |

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI |
|--------------------|-------------|----------------|------------------|-------------------|-----|
| [] | 133-0360_us | | 37.5 lm | 0 W | 80 |
| | 133-0361_us | | 41.1 lm | 0 W | 80 |
| | 133-0442 | LED-6/6W/2700K | 35.1 lm | 6 W | 80 |