

### Description

Vertically oriented, louvered steplight.

ADA (American Disabilities Act) Compliant.

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Two cable entries. Integral driver. Factory-installed LED circuit board. 0-10V Dimming standard.

A pre-installation blockout is available and recommended for mounting in concrete walls; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Luminaire body and lens frame constructed in die cast aluminum			
Lens	Opal polycarbonate lens.			
Colors	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL8019</b>	<b>RAL9007</b>
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS polymer coated stainless steel			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	120-277V / 50-60 Hz 0-10 V dimmable driver.
Driver / Ballast	Integral EC electronic converter
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)


### Additional information

Length x Width (inches)	9.84 x 3.62
Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L80B10 > 54000h

**Options**


**Light distribution**    **Color temperature**    **Nominal Watt**

[]



3000K

6 W



4000K



2700K

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
[]	133-0442	LED-6/6W/2700K	35.1 lm	6 W	80
	133-0360	LED-6/6W/3000K	37.5 lm	6 W	80
	133-0361	LED-6/6W/4000K	41.1 lm	6 W	80