

### Description

Pole or wall-mounted LED luminaire with integrated heat sinks. Side-entry mount.

IP66. Class I or Class II. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Recommended mounting height 10-30 ft, depending on lamp type selected.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	PMMA RFC Reflection Contour Lens technology			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel hardware			
Ingress protection	IP66			
Impact resistance	IK08			
Corrosion resistance	5CE			










### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral 120-277V EC electronic converter with 0-10V dimming.
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	C-D (Light source)



### Additional information

Length x Width (inches)	19.09 x 11.81
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	1.6 ft <sup>2</sup>
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

Light distribution	Color temperature	Nominal Watt
 [S60] Type III Short	 3000K	48 W 24 W
 [S70] Type II Short	 4000K	12 W 72 W
 [A60] Type IV Very Short	 2700K	
 [S65] Type III Medium		
 [R65]		
 [P65] Type II Medium		

## Configurations




Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[A60] Type IV Very Short</p>	108-2412	LED-12/12W/2700K	1487.1 lm	12 W	80
	108-1321	LED-12/12W/3000K	1589.7 lm	12 W	80
	108-1322	LED-12/12W/4000K	1743.5 lm	12 W	80
	108-2413	LED-12/24W/2700K	2637.3 lm	24 W	80
	108-1301	LED-12/24W/3000K	2832.7 lm	24 W	80
	108-1302	LED-12/24W/4000K	3028 lm	24 W	80
	108-2414	LED-24/24W/2700K	2974.2 lm	24 W	80
	108-1311	LED-24/24W/3000K	3179.4 lm	24 W	80
	108-1312	LED-24/24W/4000K	3487 lm	24 W	80
	108-2415	LED-24/48W/2700K	5274.6 lm	48 W	80
	108-1291	LED-24/48W/3000K	5665.3 lm	48 W	80
	108-1292	LED-24/48W/4000K	6056 lm	48 W	80
	108-2416	LED-24/72W/2700K	8494.7 lm	72 W	80
	108-2052	LED-24/72W/3000K	8909.1 lm	72 W	80
	108-2053	LED-24/72W/4000K	9323.5 lm	72 W	80
 <p>[P65] Type II Medium</p>	108-2417	LED-12/12W/2700K	1598.1 lm	12 W	80
	108-1883	LED-12/12W/3000K	1708.3 lm	12 W	80
	108-1884	LED-12/12W/4000K	1873.6 lm	12 W	80
	108-2418	LED-12/24W/2700K	2907.1 lm	24 W	80
	108-1879	LED-12/24W/3000K	3122.4 lm	24 W	80
	108-1880	LED-12/24W/4000K	3337.7 lm	24 W	80
	108-2419	LED-24/24W/2700K	3196.2 lm	24 W	80
	108-1881	LED-24/24W/3000K	3416.6 lm	24 W	80
	108-1882	LED-24/24W/4000K	3747.2 lm	24 W	80
	108-2420	LED-24/48W/2700K	5814.1 lm	48 W	80
	108-1877	LED-24/48W/3000K	6244.8 lm	48 W	80
	108-1878	LED-24/48W/4000K	6675.5 lm	48 W	80
	108-2421	LED-24/72W/2700K	9161.4 lm	72 W	80
	108-2054	LED-24/72W/3000K	9608.3 lm	72 W	80
	108-2055	LED-24/72W/4000K	10055.2 lm	72 W	80
108-2407	LED-12/12W/2700K	1519.5 lm	12 W	80	
108-1325	LED-12/12W/3000K	1624.3 lm	12 W	80	

## WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/04/2026


Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
 [R65]	108-1326	LED-12/12W/4000K	1781.5 lm	12 W	80	
	108-2408	LED-12/24W/2700K	2694.7 lm	24 W	80	
	108-1305	LED-12/24W/3000K	2894.4 lm	24 W	80	
	108-1306	LED-12/24W/4000K	3094 lm	24 W	80	
	108-2409	LED-24/24W/2700K	3039 lm	24 W	80	
	108-1315	LED-24/24W/3000K	3248.6 lm	24 W	80	
	108-1316	LED-24/24W/4000K	3563 lm	24 W	80	
	108-2410	LED-24/48W/2700K	5389.5 lm	48 W	80	
	108-1295	LED-24/48W/3000K	5788.7 lm	48 W	80	
	108-1296	LED-24/48W/4000K	6187.9 lm	48 W	80	
	108-2411	LED-24/72W/2700K	8943.7 lm	72 W	80	
	108-2056	LED-24/72W/3000K	9380 lm	72 W	80	
	108-2057	LED-24/72W/4000K	9816.3 lm	72 W	80	
 [S60] Type III Short	108-2392	LED-12/12W/2700K	1603.4 lm	12 W	80	
	108-1317	LED-12/12W/3000K	1714 lm	12 W	80	
	108-1318	LED-12/12W/4000K	1879.9 lm	12 W	80	
	108-2393	LED-12/24W/2700K	2880.9 lm	24 W	80	
	108-1297	LED-12/24W/3000K	3094.3 lm	24 W	80	
	108-1298	LED-12/24W/4000K	3307.7 lm	24 W	80	
	108-2394	LED-24/24W/2700K	3206.8 lm	24 W	80	
	108-1307	LED-24/24W/3000K	3428 lm	24 W	80	
	108-1308	LED-24/24W/4000K	3759.8 lm	24 W	80	
	108-2395	LED-24/48W/2700K	5761.8 lm	48 W	80	
	108-1287	LED-24/48W/3000K	6188.6 lm	48 W	80	
	108-1288	LED-24/48W/4000K	6615.4 lm	48 W	80	
	108-2396	LED-24/72W/2700K	9244.4 lm	72 W	80	
	108-2058	LED-24/72W/3000K	9695.3 lm	72 W	80	
	108-2059	LED-24/72W/4000K	10146.2 lm	72 W	80	
	 [S65] Type III Medium	108-2397	LED-12/12W/2700K	1613.9 lm	12 W	80
		108-1323	LED-12/12W/3000K	1725.2 lm	12 W	80
108-1324		LED-12/12W/4000K	1892.2 lm	12 W	80	
108-2398		LED-12/24W/2700K	2913.1 lm	24 W	80	
108-1303		LED-12/24W/3000K	3128.9 lm	24 W	80	

## WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 04/04/2026

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	108-1304	LED-12/24W/4000K	3344.7 lm	24 W	80
	108-2399	LED-24/24W/2700K	3227.9 lm	24 W	80
	108-1313	LED-24/24W/3000K	3450.5 lm	24 W	80
	108-1314	LED-24/24W/4000K	3784.4 lm	24 W	80
	108-2400	LED-24/48W/2700K	5826.2 lm	48 W	80
	108-1293	LED-24/48W/3000K	6257.8 lm	48 W	80
	108-1294	LED-24/48W/4000K	6689.4 lm	48 W	80
	108-2401	LED-24/72W/2700K	9349 lm	72 W	80
	108-2060	LED-24/72W/3000K	9805 lm	72 W	80
	108-2061	LED-24/72W/4000K	10261.1 lm	72 W	80
	108-2402	LED-12/12W/2700K	1591.6 lm	12 W	80
108-1319	LED-12/12W/3000K	1701.4 lm	12 W	80	
108-1320	LED-12/12W/4000K	1866 lm	12 W	80	
108-2403	LED-12/24W/2700K	2822.6 lm	24 W	80	
108-1299	LED-12/24W/3000K	3031.7 lm	24 W	80	
108-1300	LED-12/24W/4000K	3240.8 lm	24 W	80	
108-1309	LED-24/24W/3000K	3402.8 lm	24 W	80	
108-1310	LED-24/24W/4000K	3732.1 lm	24 W	80	
108-2405	LED-24/48W/2700K	5645.2 lm	48 W	80	
108-1289	LED-24/48W/3000K	6063.4 lm	48 W	80	
108-1290	LED-24/48W/4000K	6481.5 lm	48 W	80	
108-2406	LED-24/72W/2700K	9256.3 lm	72 W	80	
108-2062	LED-24/72W/3000K	9707.9 lm	72 W	80	
108-2063	LED-24/72W/4000K	10159.4 lm	72 W	80	

[S70] Type II Short